



### Stationary machines for wall mount are equipped with:

- Triplex, positive displacement pump delivers a smooth, constant flow and pressure. The downstream restriction will require adjustment or a valve to regulate any changes in pressure.
- Pressure regulator.
- Safety valve.
- Stainless steel pressure gauge.
- Stainless steel Maintenance free selector valve for water, chemicals and air.
- Stainless steel brake tank – 12liter.
- Water filter.
- 2 separated chemical injectors with adjustable dosing ratio (0.15-15%) who makes it impossible to mix-up chemicals.
- Stainless steel cabinet, with sloped top cover for optimal hygiene.
- 2 x stainless steel check valves on chemical suction.
- 1 x blue suction kit with filter and PVC pipe for foam cleaning chemical.
- 1 x yellow suction kit with filter and PVC pipe for disinfection chemical.
- Set Of dosing tips.
- SWL: security water level system. Stops the machine in case of water lack.
- TST: automatically stops the machine (in standby)after 25 Sec. use.
- SBS: automatically complete shut off after 60min in total stop.
- DSS: Drop stop system, total stop system if there are leakages.
- Optional mobile skid in stainless steel, with hose reel, hose, spray gun, container support...
- Optional TMM hot water pump up till 85°C.
- Optional Stainless steel wall supports.
- Optional accessories on page 7 and 8.



*Mounting example, Hose reel, skid and accessories not included.*

### Mobile version is extra equipped with:

- Click & clean main station with integrated satellite. See here above.
- Stainless steel heavy duty trolley
- 2 x big wheels on the back
- 2 x stainless steel swivel wheels with brake in the front.
- Container holder for 2 x 25 liter cans.
- Stainless steel automatic spring driven hose reel.
- 20 meter 5 layer hose with reinforcements, Max. 400bar /150°C.
- Stainless steel Spray gun with quick coupling and "Low trigger force" technology.



## Advantages of the HPJET machines

### ➤ 100% AIR free foaming system

- HPJET units create foam without the addition of compressed air. The foam is created via a dynamic foam lance that sucks air from the environment through the water passage in the lance.
- Foam is created at the end of the lance and no longer in the satellite. Because of this there is no longer "foam" who is transferred through the wash down hoses with quality loss depending on the length of the wash down hose.
- Because of this advantage we can use up to 60 meter lengths of wash down hoses without any foam quality loss.

### ➤ Investment reduction

- Long wash down hoses reduces the investment costs with minimal 65%. Because of the 3 x longer hose lengths it reduces the number of cleaning systems in the production zone by 65%  
Bonus: lower costs for mounting water supply and compressed air pipes.

### ➤ Safety features

- ❖ **No danger for other machines and compressed air equipment in the production area**
- The danger of compressed air lines, compressors, compressed air valves, pistons, air regulators ... being destroyed in other machines because of possible leakage of chemicals into the compressed air supply via cleaning satellites is non-existent.
- ❖ **No danger of chemical mixing with the water network.**
- Every HPJET unit is equipped with a brake tank what makes it impossible to unintentionally suck chemicals back into the water network via vacuum. No security valve is required to connect this system.
- ❖ **Self-protective system.**
- SWI: security water level system. Stops the machine in case of water lack.

### ➤ Energy friendly

- TST: automatically stops the machine (in standby) after 25 Sec. use.
- SBS: automatically complete shut off after 60min in total stop.
- DSS: Drop stop system, Total stop system if there are leakages.

### ➤ Continuity and reliability.

- Every system works independently of each other.  
In standard cleaning systems, usually 1 pump system is used for supplying water pressure to all cleaning satellites. Every HPJET system has its own pump. This guarantees continuity in the cleaning process if one pump should fail.


➤ **User friendly.**

- Because there is no longer transfer of foam through the wash down hoses a Smaller and more flexible wash down hose is used.
- Wide range of accessories to make the complete cleaning process efficient and easy. Tank cleaning, conveyor cleaning, sewer and drain cleaning.


➤ **Mistake proof - impossible to make mistakes.**

- Only 1 lever to select positions. It is impossible to select different positions at the same time
- The system is equipped with 2 chemical injectors that are 100% separate from each other. If there is switching between the different chemicals, it will always pass by the automatic flushing.
- Chemical suction hoses in colour code.
- Automatic pressure reduction / mounting by switching lances.

**Mounting HPJET unit.**



HPJET units are assembled in such a way that all parts are easily accessible for maintenance. The unit is CE approved.



### Technical data Click & clean HPJET Series

Reference	100.140	100.144	100.146	100.146XM
<b>Model</b>	HPJET15	HPJET21	HPJET30	HPJET30 mobile
<b>Inlet supply pressure:</b>	2 - 6 bar			
<b>Minimal supply flow:</b>	20Lpm	25Lpm	35Lpm	35Lpm
<b>Outlet flow range:</b>	15 Lpm	21 Lpm	30 Lpm	30 Lpm
<b>*Max. water temperature:</b>	45°C/*85°C	45°C/*85°C	45°C/*85°C	45°C/*85°C
<b>Rinse pressure:</b>	20-200 bar	20-200 bar	40-200 bar	40-200 bar
<b>Chemical injectors:</b>	2	2	2	2
<b>Chemical dosing ratio:</b>	0.15 - 15%	0.15 - 15%	0.15 - 15%	0.15 - 15%
<b>Functions:</b>	<ul style="list-style-type: none"> <li>• Foam</li> <li>• Disinfect</li> <li>• Rinse</li> </ul>	<ul style="list-style-type: none"> <li>• Foam</li> <li>• Disinfect</li> <li>• Rinse</li> </ul>	<ul style="list-style-type: none"> <li>• Foam</li> <li>• Disinfect</li> <li>• Rinse</li> </ul>	<ul style="list-style-type: none"> <li>• Foam</li> <li>• Disinfect</li> <li>• Rinse</li> </ul>
<b>Voltage:</b>	3x400V 50Hz	3x400V 50Hz	3x400V 50Hz	3x400V 50Hz
<b>Dimensions cm (WxHxD):</b>	950x540x455mm	950x540x455mm	950x540x455mm	1180x1200x750 mm
<b>Power:</b>	5.5 kW	7.5kW	11Kw	11Kw

\*Optional 85°C. incoming water temperature. See accessories.